

PRODUCT SPECIFICATION

BRAIDED SLEEVING

UL94 HB

- *General*

The braided sleeveings are manufactured with single filament of first quality. The sleeveings are radially expandable by means of longitudinal movement that makes it possible to obtain a double diameter.

This characteristic makes insertion of electrical cables to be protected very easy. The sleeveings are available in standard color black but can also be ordered in gray. The sleeving comes in a handy minibox.

Based on volumes other colors can be produced.

[E-number list](#) chapter:
4.4.1



- *Standard Sizes*

E-number	Art. code	Description
0768412	29150040S-MB	4-8 mm 200 meter
0768413	29150050S-MB	5-10 mm 100 meter
0768414	29150100S-MB	10-20 mm 100 meter
0768415	29150150S-MB	15-30 mm 100 meter
0768416	29150200S-MB	20-35 mm 50 meter
0768417	29150400S-MB	40-70 mm 50 meter
0768418	29150500S-MB	50-80 mm 50 meter

- *General properties*

Manufactured with polyester monofilaments, this braid can be over expanded pushing back mechanically.

Specific weight	ISO R1183	1,38g/cm ³
Traction resistance	ISO 37	4,80kg/mm ²
Elongation at break	ISO 37	28-35%
Working temperature		-50°C till +150°C
Melting point		260 °C

Visit
www.tibe.se

E-mail
tibe@tibe.se

Call
 +46(0)8-546 80 200