

PRODUCT SPECIFICATION

BRAIDED SLEEVING

UL94 V0 FIRE PROOF

- *General*

The braided sleeveings are manufactured with single filament of first quality. The sleeveings are radially expandable by means of longitudinal movement that makes it possible to obtain a double diameter. This characteristic makes insertion of electrical cables to be protected very easy. The sleeveings are available in standard color black but can also be ordered in gray. Based on volumes other colors can be produced.



- *Standard Sizes*

E-number	Art. code	Description
	29150040SV0	4-8 mm 200 meter
	29150050SV0	5-10 mm 100 meter
	29150100SV0	10-20 mm 100 meter
	29150150SV0	15-30 mm 100 meter
	29150200SV0	20-35 mm 50 meter
	29150400SV0	40-70 mm 50 meter
	29150500SV0	50-80 mm 50 meter

- *General properties*

Manufactured with polyester monofilaments, this braid can be over expanded pushing back mechanically.

Specific weight	ISO R1183	1,5g/cm ³
Traction resistance	ISO 37	5,28kg/mm ²
Elongation at break	ISO 37	39%
Working temperature		-50°C till +150°C
Melting point		235 °C

Visit
www.tibe.se

E-mail
tibe@tibe.se

Call
 +46(0)8-546 80 200