

PRODUCT SPECIFICATION

OPTICAL FIBER INSPECTION, TEST AND MEASUREMENT

JDSU FBP HP3-60-P4 SYSTEM

Avoid unnecessary welding, cleaning and contamination with JDSU FBP HP3-60-P4 SYSTEM. Always inspect connectors and adapters before connecting. Raise the bar for installations and maintenance while reducing work time. Two microscopes and a power meter in one single system.

- Two microscopes and built in power meter
- Identify particles/scratches smaller than 1 μm
- 1.8-inch TFT LCD
- 400x magnification for patch cord with display unit microscope
- Dual magnification (200/400x) probe microscope
- Measures optical power at 850, 1300, 1310, 1490 and 1550 nm
- For all single and multi mode applications, such as LAN, TELECOM, CATV and DWDM
- 162x114x42 mm (display unit), 46x43x140 mm (probe microscope)
- 333 g, including six AA batteries
- 3 hours run time (battery)



Product **JDSU FBP HP3-60-P4 System**
Tibe Art.nr. **DM-0131**

Included	Dual magnification (200/400x) FBP video probe microscope Handheld inspect and test display system with integrated power meter and 400x PCM Interchangeable FBPT inspection tips (2) in hard case: SC-PC bulkhead LC-PC bulkhead Interchangeable FMAE adapters (2) for PCM in hard case: Universal 2.5 mm PC patch cord Universal 1.25 mm PC patch cord Carrying case
Accessories	Probe Tip SC/APC Bulkhead. Tibe Art.nr: DM-0325 Probe Tip SC, ST, FC/APC Patch Cord. Tibe Art.nr: DM-0330

Visit
www.tibe.se
E-mail
tibe@tibe.se
Call
+46(0)8-546 80 200



1. Inspect patch cord



2. Switch to probe



3. Inspect adapter



4. Connect



5. Measure